

PIPE-LINE: DATOS TÉCNICOS – CON SUJECCIÓN EXTERIOR

Modelo	Rango de trabajo	Espesor máx. de la pared	Potencia del motor	Peso
C-Biter 63E	32 – 63 mm	12 mm	1300 W	9 kg
C-Biter 76E	42 – 76 mm	12 mm	1300 W	10 kg
C-Biter 89E	63 – 89 mm	12 mm	1300 W	14 kg
C-Biter 114E	76 – 114 mm	12 mm	1300 W	15 kg
Phyton 63ESC	14 – 63 mm	12 mm	1300 W	13 kg
Phyton 114ESC	57 – 114 mm	12 mm	1300W	17 kg
Phyton 89ES	63 – 89 mm	12 mm	1300 W	14 kg
Phyton 168ES	50 – 168 mm	80 mm	2000 W	50 kg
Phyton 230ES	80 – 230 mm	80 mm	2000 W	53 kg
Phyton 275ES	125 – 275 mm	80 mm	2000 W	56 kg
Phyton 305ES	150 – 305 mm	80 mm	2000 W	63 kg
Phyton 325ES	168 – 325 mm	80 mm	2000 W	65 kg
Phyton 377ES	219 – 377 mm	80 mm	2000 W	68 kg
Phyton 426ES	273 – 426 mm	80 mm	2000 W	75 kg
Phyton 457ES	300 – 457 mm	80 mm	2000 W	80 kg
Phyton 508ES	355 – 508 mm	80 mm	2400 W	102 kg
Phyton 560ES	400 – 560 mm	80 mm	2400 W	110 kg
Phyton 610ES	457 – 610 mm	80 mm	2400 W	115 kg
Phyton 630ES	480 – 630 mm	80 mm	2400 W	120 kg
Phyton 660ES	508 – 660 mm	80 mm	2400 W	126 kg
Phyton 715ES	560 – 715 mm	80 mm	2400 W	138 kg
Phyton 762ES	600 – 762 mm	80 mm	2400 W	150 kg
Phyton 830ES	660 – 813 mm	80 mm	2400 W	158 kg
Phyton 914ES	762 – 914 mm	80 mm	2400 W	178 kg